

## ezW300I/WR



### Technical characteristics

Diameter	300 mm
Type of Tyre	PU 80 sh.A - Flat profile
Speed range (traction)	0 to 9 km/h
Peak pushing effort	35 daN Moves 1000 kg
Nominal performance	12 daN at 6 km/h
Maximum rolling speed	12 km/h
Battery capacity	240 Wh
Function(s)	Regen charge (towing)

- ✓ ez-Wheel® autonomous wheel **ezW300I/WR** - Series 300
- ✓ developed for intensive use in industry
- ✓ suitable for:
  - industrial handling tools
  - towed rolling equipment
  - trolleys
  - pusher/pullers

### Component specifications

#### Motor



Technology	BLDC PM
Gearbox	1-stage helical
Indicative lifespan*	5 000 h / 15 000 km 1 500 000 starts/stops
Nominal speed	110 rpm (6,2 km/h)
Nominal power	200 W (S1)
Peak torque	52 Nm

#### Battery



Electrochemistry	Ni-MH long life
Energy	240 Wh
Indicative lifespan*	5-8 years
Recharge mode	Charger Towing
Minimum charging time*	2.5 hours (to 90%)

#### Interface



Wired	-
Wireless	LR WPAN 2.4 GHz IEEE 802.15.4

### Conditions of use



Temperatures	-20 to +60 °C
IP index	IP54
Maintenance period*	5-7 years

The wheel can be used inside or outside, over a wide range of temperatures. The components – including the battery – do not need any inspection or maintenance over the product's whole lifespan.

### Weight



Wheel weight	17 kg
Maximum vertical load	300 kg 260 kg at 4 km/h 130 kg at 12 km/h

The robust assembly can withstand the stresses of knocks and severe vibration and enables the wheel to carry some load.

*ez-Wheel products are guaranteed 1 year from the date of purchase and 2 years against production defects. Consult the general conditions of sale for more information.*

All values are subject to changes without prior notice.

\*: Values for reference, based on standard condition testing, may vary with different application cases.

ez-wheel.com